

MULTIPLIER
 []


MODEL 3506 / 3506LB POWERMAX COUPLING

One range fits all pipe ODs IPS PVC to Rough Barrel AC

CENTER BARREL: Ductile Iron per ASTM A536 and AWWA C219.

END GLANDS: Ductile Iron per ASTM A536 and AWWA C219.

GASKET: SBR transition design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water and salt media with a temperature range of -40° F to +150° F.

BOLTS & NUTS: Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C219.

FINISH: Epoxy.

Pipe Size			Pipe OD Ranges		Standard Barrel List Price	Standard Barrel List Price w/SST N&Bs	Long Barrel List Price	Long Barrel List Price w/SST N&Bs	Standard Weight		Standard Barrel Length		Long Barrel Weight		Long Barrel Length	
in.	mm.		in.	mm.					lbs.	kgs.	in.	mm.	lbs.	kgs.	in.	mm.
2	50	A	2.30-2.90	58-74					16	7.5	5	125	21	9	12	300
3	80	A	3.40-4.20	86-107					21	9.5	5	125	30	13	12	300
4*	100	A	4.20-5.33	107-135					27	12.5	6	150	37	17	12	300
6*	150	A	6.25-7.45	159-189					36	16.5	6	150	52	23	12	300
8*	200	A	8.40-9.79	214-249					60	27.5	10	250	65	30	12	300
10	250	A	10.45-12.12	272-308					69	31.5	10	250	83	38	12	300
12	300	A	12.50-14.38	324-365					83	37.5	10	250	113	51	12	300
14	350	A	15.25-16.90	387-429					130	59	12	300	N/A	N/A	N/A	N/A
16	400	A	16.00-17.80	406-452					155	70.5	12	300	N/A	N/A	N/A	N/A
		B	17.40-19.00	442-483					165	75	12	300	N/A	N/A	N/A	N/A

HOW TO ORDER: Specify Model Number, Pipe Size with Letter Code(s) if applicable. EXAMPLE: 6" Steel O.D. 6.63 to 6" Asbestos Cement O.D. 7.37. Order 3506 - 6A.

*Note: Pipe diameters less than IPS/STEEL rated up to 50 psi work pressure.



PROVIDED AS A COURTESY BY:

PACIFIC

PIPELINE SUPPLY

907.833.9932

fax: 940.723.8378

www.powerseal.com

Material Specifications Subject to Change