

# CAST COUPLINGS



MULTIPLIER



## MODEL 3504 COMPRESSION COUPLING

**CENTER BARREL:** Carbon Steel per AISI C1010-15.

**END GLANDS:** Malleable Iron per ASTM A47.

**GASKET:** NBR suitable for oil, mild acids, water, and salt media with a temperature range of -40° F to +212° F.

**FINISH:** Galvanized.

Pipe Size		Pipe OD		Box Weight		Body Length		Box Quantity	List Price
in.	mm.	in.	mm.	lbs.	kgs.	in.	mm.		
1/2	15	0.84	21	19	9	4	102	25	
3/4	20	1.05	27	19	9	4.4	111	15	
1	25	1.32	34	16	7	4.5	114	10	
1 1/4	32	1.66	42	12	5	4.5	114	6	
1 1/2	40	1.9	48	15	7	5	127	6	
2	50	2.38	60	21	10	5.4	137	6	



## MODEL 3506AS POWERMAX COUPLING

One range fits all pipe ODs IPS PVC to Rough Barrel AC

**CENTER BARREL:** Type 304 (18-8) Stainless Steel.

**END GLANDS:** Type 304 (18-8) Stainless Steel.

**GASKET:** SBR transition design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per ASTM D2000. Suitable for mild acids, water and salt media with a temperature range of -40° F to +150° F.

**BOLTS & NUTS:** Type 304 (18-8) Stainless Steel per ASTM A193 and A194.

**NOTE:** Hex nuts are furnished with fusion bonded coating to prevent seizing and galling.

Pipe Size			Pipe OD Ranges		List Price	Weight		Barrel Length		Bolt Qty.
in.	mm.		in.	mm.		lbs.	kgs.	in.	mm.	
2	50	A	2.30-2.90	58-74		11	5	5	125	2
3	80	A	3.40-4.20	86-107		14	6.5	6.5	165	3
4*	100	A	4.20-5.33	112-135		18	8.5	6	150	4
6*	150	A	6.25-7.45	166-189		24	11	6	150	5
8*	200	A	8.40-9.79	217-249		40	16.5	10	250	6
10	250	A	10.70-12.12	272-293		46	21	10	250	7
12	300	A	12.75-14.38	322-345		56	25.5	10	250	8

HOW TO ORDER: Specify Model Number, Pipe Size with Letter Code(s) if applicable. EXAMPLE: 6" Steel O.D. 6.63 to 6" Asbestos Cement O.D. 7.37. Order 3506AS - 6A.

\*Note: Pipe diameters less than IPS/STEEL rated up to 50 psi work pressure.



800.800.0932

fax: 940.723.8378

www.powerseal.com

09.08

Material Specifications Subject to Change