

ROMAC INDUSTRIES, INC.

STYLE EC501 END CAP COUPLING

SUBMITTAL INFORMATION

MATERIALS

| | |
|----------------|--|
| Castings | The end rings, center rings end cap are cast from ductile (nodular) iron, meeting or exceeding ASTM A 536-80, Grade 65-45-12. |
| End Cap | Color coded black to be used with cast iron size 501 gasket. End caps are furnished with 2" IPT female threads with plug. |
| Gaskets | Gaskets are made from virgin Styrene Butadiene Rubber (SBR) compounded for water and sewer service in accordance with ASTM D2000 MBA 710 - 90. Other compounds available for petroleum, chemical, or high temperature service. |
| Bolts and Nuts | 5/8 inch, High strength low alloy steel trackhead bolts. National coarse rolled thread and heavy hex nuts. Steel meets AWWA C-111-80 composition specifications. Stainless steel bolts and nuts available. |
| Coatings | Shop coat applied to cast parts for corrosion protection in transit. Fusion bonded epoxy, liquid epoxy and other coatings available on request. |

PRESSURE

When properly installed on a pipe that is within the correct outside diameter range, couplings in the Romac Style 501 line can be used at working pressures up to 250 psi. Higher working pressures available for specific applications.

Note: Couplings do not provide protection against possible pullout of pipe ends in unrestrained conditions

SIZES AND RANGES

See catalog.

9/06

This information is based on the best data available at the date printed above, please check with Romac Engineering Department for any updates or changes.