



# INDUSTRIAL THREADED PRODUCTS INC.

13580 FIRESTONE BLVD. , SANTA FE SPRINGS, CA 90670

800-976-BOLT FX: 800 646 4249

www.itpbolt.com

# NON-ASBESTOS GASKET GARLOCK 3000

## SUBMITTAL SPECIFICATIONS

*GASKETS MEET THE PRESSURE RATINGS, DRILLING AND  
DIMENSIONS OF ANSI / ASME B16.21*

### TECHNICAL DATA

PRODUCT	STYLE	COLOR	BINDER	TEMP MAX	PRESSURE MAX	PRESS.X TEMP MAX	COMPRESS. ASTM F-36	RECOVERY ASTM F-36	TENSILE STRENGTH ASTM F152	FLEXIBILITY	CREEP RELAXATION ASTM F-78
GARLOCK	3000	BLUE/GRN	NBR	700°	1000 PSI	350,000	7-17	59.6%	2256	PASSED	24

### AVAILABILITY

FULL FACE     RING     1/16"     1/8"     1/4"

**SERVICE:** Suitable against, Water, Brine, Sludge, Organic and Weak In-Organic Acids, Concentrated and Diluted Alkalis (PH Range From 1 to 11), Chemicals, Petroleum and Petroleum Derivatives, Synthetic Oils, Animals Fats, Vegetable Oils, Aromatic and Aliphatic Solvents, and Chlorinated Solvents. These Gasket materials meet the pressure ratings, drilling and dimensional requirements of ANSI/ASME B16.2.1 and AWWA C207-94.

**GENERAL DESCRIPTION:** Manufactured from a Non-Asbestos Material formulated for services in most sealing applications as a universal replacement gasket. The synthetic fiber content is Aramid Bound by Nitrile Rubber (NBR). These gaskets have a non-stick coating.

12027 Arrow Route  
Rancho Cucamonga, CA 90670  
909-466-9445  
fx: 909-945-2696

2145 South 11th Ave. Ste 130  
Phoenix, AZ 85007-4199  
800-976-2658  
fx:800-646-4249

174 Lawrence Drive Ur  
Livermore, CA 94550  
800-566-8831  
fx: 800-646-4249

