

ROMAC INDUSTRIES, INC.
"600" SERIES
PIPE RESTRAINING SYSTEM
SUBMITTAL INFORMATION

USE The Series 600 is a multi-purpose pipe restraint system for PVC and ductile iron pipe joints. Configurations are available for us on bell and spigot joints, push-on fittings with restraint ears, mechanical joints, Romac Style 501 and 511 flex couplings. They are engineered to eliminate the need for thrust blocks or other methods of restraint. Not for use on polyethelene pipe, plain end mechanical joint fittings or steel pipe.

MATERIALS

Castings The restrainer rings are cast from ductile (nodular) iron, meeting or exceeding ASTM A 536, Grade 65-45-12.

Restraining Fasteners 3/4" Restraining rods, T-bolts, heavy hex nuts, and coupling nuts are high strength low alloy steel meeting AWWA C111 composition specifications. National coarse thread. Allowable force per bolt is 7,500 pounds when properly installed.

Clamping Fasteners The 4" and 6" sizes use high strength low alloy steel trackhead bolts. Steel meets AWWA C111 composition specifications. National coarse rolled thread and heavy hex nuts. The 8" through 12" sizes use heavy hex Grade 8 bolts. Sizes 4" and 6" use 5/8", 8" 3/4", 10" and 12" use 7/8".

Coatings Shop coat applied to cast parts for corrosion protection in transit.

PRESSURE

When properly installed on the correct size pipe, the Romac Series "600" Restraining System can be used at these working pressures:

Pipe Material	Pressure Rating	Test Pressure	Safety Factor
PVC	Up to 200 psi	1.25 times Rating of Pipe	2:1
Ductile Iron	150 psi	188 psi	2:1

Approvals: **FM** approved for AWWA C900 PVC pipe, 4 through 10 inch, at 150 psi working pressure and 225 psi test.

SIZES

See Catalog.

3/11

This information is based on the best data available at the date printed above; please check with Romac Engineering Department for any updates or changes.

Phone (425) 951 6200 • Toll Free 1 800 426 9341 • Fax (425) 951 6201 • www.romacindustries.com