



RieberLok™ Gasket for Internal Restraint of AWWA C900 PVC Pipe & Fittings Originally Fitted with a Rieber Gasket



SUBMITTAL INFORMATION

PROJECT NAME:

ENGINEER:

CONTRACTOR:

SPEC. SECTION:



DATE:

Features and Benefits

- RieberLok is an internal restraint eliminating common external steel corrosion issues.
- RieberLok has the same installation procedure as the Rieber gasket which reduces chance of installation error.
- RieberLok saves significant time and labor over bell harnesses, keeping labor costs lower.
- The RieberLok Gasket can be easily installed outside of the ditch which is safer, faster, cleaner, and easier.
- RieberLok is a single gasket which makes for easier management due to less inventory space and lower freight costs than external restraints with multiple pieces.
- RieberLok can be installed at the pipe plant or in the field.

General Information:

- Gasket teeth are made of Stainless Steel
- Pressure rated equal to the working pressure rating of the pipe with a 2:1 safety factor.
- Size range of 4" - 16"
- Maintains full deflection of PVC Pipe joints and fittings.
- Assembly instructions, field cut instructions, and FAQs on www.RieberLok.com
- Works on C900 DR-14, DR-18, and DR-25



Gasket Material Options:

SBR



Registered Trademark of Ransom International, LLC.
Ransom International, LLC.
David Martin (205)-397-9464
www.RieberLok.com